

Двуредов теплообменник		Режим отопление					Режим охлаждения				
Типоразмер		T _{вх, в-х} = -12°C/88% р.н.; T _{вода} = 80/60°C					T _{вх, в-х} = 33°C/32% р.н.; T _{вода} = 7/12°C				
	V _{в-х}	Q _{от}	T _{изх, в-х}	dP _{в-х}	V _{вода}	dP _{вода}	Q _{охл}	T _{изх, в-х}	dP _{в-х}	V _{вода}	dP _{вода}
	[м³/ч]	[kW]	[°C]	[Pa]	[м³/ч]	[kPa]	[kW]	[°C]	[Pa]	[м³/ч]	[kPa]
RWW 400/200-2	750	9.3	21	42	0.41	7.6	2.4	23	29	0.41	10
RWW 500/250-2	1200	15.2	22	44	0.67	24	4.2	22	31	0.7	35.3
RWW 500/300-2	1500	19	22	47	0.83	42.3	5	22	33	0.9	65
RWW 600/300-2	1800	23	22	46	0.99	20.7	6	22	33	1.02	29.9
RWW 600/350-2	2100	26	21	46	1.15	32.3	7	23	32	1.23	48.7
RWW 700/400-2	3000	36	21	52	1.61	33.7	9	23	35	1.31	32.8
RWW 800/500-2	4000	51	22	47	2.3	43	14	22	33	2.4	67
RWW 1000/500-2	5500	67	21	55	2.95	51.2	19	22	38	3.2	79.3
RWW 400/400-2	1500	20	23	42	0.85	54.2	5.5	22	30	0.93	85.2
RWW 500/500-2	2500	32	22	46	1.4	26	9	22	33	1.43	37.1
RWW 600/600-2	3500	44	22	45	1.93	21.7	12	23	31	2	31.1
RWW 800/800-2	6000	77	23	44	3.4	40	22	22	31	3.7	60
RWW 1000/1000-2	10000	136	24	54	5.97	25.9	38	21	43	6.6	37.3

Четириредов топлообменник		Режим отопление					Режим охлаждане				
Типоразмер		T _{вх, в-х} = -12°C/88% р.Н.; T _{вода} = 80/60°C					T _{вх, в-х} = 33°C/32% р.Н.; T _{вода} = 7/12°C				
	V _{в-х}	Q _{от}	T _{изх, в-х}	dP _{в-х}	V _{вода}	dP _{вода}	Q _{охл}	T _{изх, в-х}	dP _{в-х}	V _{вода}	dP _{вода}
	[m³/h]	[kW]	[°C]	[Pa]	[m³/h]	[kPa]	[kW]	[°C]	[Pa]	[m³/h]	[kPa]
RWK 400/200-4	750	15	45	83	0.66	6.5	4	19	61	0.64	7.9
RWK 500/250-4	1200	24	42	87	1.05	10	6.5	19	65	1.07	13.6
RWK 500/300-4	1500	30	41	92	1.3	11.4	8	19	69	1.32	15.3
RWK 600/300-4	1800	36	42	93	1.58	14.2	10	18	70	1.67	21
RWK 600/350-4	2100	42	42	93	1.84	14.4	12	18	70	1.95	21.2
RWK 700/400-4	3000	58	40	103	2.57	12.7	16	18	77	2.66	18
RWK 800/500-4	4000	78	41	95	3.5	5.7	20	19	70	3.3	6.8
RWK 1000/500-4	5500	106	40	110	4.65	11.1	28	19	80	4.7	14.4
RWK 400/400-4	1500	31	42	85	1.33	11.6	9	18	65	1.4	16.6
RWK 500/500-4	2500	51	42	93	2.4	39	15	17	70	2.5	63
RWK 600/600-4	3500	72	43	89	3.2	32	21	17	66	3.5	51.5
RWK 800/800-4	6000	123	43	88	5.4	35.1	35	17	67	5.98	56
RWK 1000/1000-4	10000	210	44	105	9.22	18.5	55	18	90	9.42	22.7