

	V/50Hz	RPM	Qmax [m³/h]	I [A]	P [W]	Lpa @ 3 m [dBA]	Tmin/max [°C]
APFV-L 200 2M	230	2300	860	0.26	55	50	-30/+60
APFV-L 250 2M	230	2400	1050	0.40	80	60	-30/+60
APFV-L 250 2T	400	2600	1060	0.22	80	60	-30/+60
APFV-L 250 4M	230	1380	800	0.22	50	55	-30/+60
APFV-L 250 4T	400	1400	850	0.17	60	55	-30/+60
APFV-L 300 2M	230	2300	2230	0.66	145	60	-30/+60
APFV-L 300 2T	400	2350	2310	0.25	145	60	-30/+60
APFV-L 300 4M	230	1350	1340	0.35	75	58	-30/+60
APFV-L 300 4T	400	1380	1310	0.22	75	58	-30/+60
APFV-L 350 4M	230	1380	2500	0.65	140	62	-30/+60
APFV-L 350 4T	400	1380	2520	0.38	140	62	-30/+60
APFV-L 400 4M	230	1380	3580	0.82	180	63	-30/+60
APFV-L 400 4T	400	1380	3740	0.47	180	64	-30/+60
APFV-L 450 4M	230	1350	4680	1.20	250	64	-30/+60
APFV-L 450 4T	400	1360	5280	0.60	250	65	-30/+60
APFV-L 500 4M	230	1300	7060	1.95	420	69	-30/+60
APFV-L 550 4M	230	1300	8800	2.55	550	70	-30/+60
APFV-L 550 4T	400	1350	9700	1.50	750	73	-30/+60
APFV-L 630 4M	230	1360	11900	3.50	750	75	-30/+60
APFV-L 630 4T	400	1320	12200	1.60	800	78	-30/+60
APFV-L 630 6M	230	850	10900	2.40	540	72	-40/+70