

	b2	n1xp	n2xp	n°	ø	I	J	K	L	M	N	O	P	Q	R	S	T	U	ø	Kg
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	
VC 500/N2	136	-	-	4	10	121	-	-	45	211	45	203	225	-	-	-	-	-	10	63
VC 560/N2	145	-	-	4	10	133	-	-	58	246	55	234	260	-	-	-	-	-	10	95
VC 560/N2	145	-	-	4	10	133	-	-	58	246	55	234	260	-	-	-	-	-	10	98
VC 630/N2RI	155	-	1x100	6	10	133	-	-	58	246	55	234	260	-	-	-	-	-	10	125
VC 630/N2RI	155	-	1x100	6	10	197	-	-	58	246	30	289	324	-	-	-	-	-	12	124
VC 630/N2	155	-	1x100	6	10	197	-	-	49	276	30	289	324	-	-	-	-	-	12	130
VC 630/N2	155	-	1x100	6	10	197	-	-	49	276	30	289	324	-	-	-	-	-	12	134
VC 710/N2RI	175	-	1x112	6	12	237	-	-	49	276	40	289	372	-	-	-	-	-	12	162
VC 710/N2RI	175	-	1x112	6	12	237	-	-	49	336	40	337	372	-	-	-	-	-	12	175
VC 710/N2	175	-	1x112	6	12	237	-	-	59	336	40	337	372	-	-	-	-	-	12	179
VC 710/N2	175	-	1x112	6	12	237	-	-	59	336	40	337	372	-	-	-	-	-	12	185
VC 800/N2RI	187	-	1x112	6	12	237	-	-	59	336	40	337	372	-	-	-	-	-	12	219
VC 800/N2RI	187	-	1x112	6	12	237	-	-	59	336	40	337	372	-	-	-	-	-	12	227
VC 800/N2	187	-	1x112	6	12	237	-	-	59	336	40	337	372	-	-	-	-	-	12	232
VC 800/N2	187	-	1x112	6	12	337	-	-	49	436	50	395	440	-	-	-	-	-	14	256
VC 900/N2RI	201	-	1x112	6	12	337	-	-	49	436	50	395	440	-	-	-	-	-	14	357
VC 900/N2RI	201	-	1x112	6	12	337	-	-	49	436	50	395	440	-	-	-	-	-	14	363
VC 900/N2	201	-	1x112	6	12	337	-	-	49	436	50	395	440	-	-	-	-	-	14	369
VC 900/N2	201	-	1x112	6	12	337	-	-	49	436	50	395	440	-	-	-	-	-	14	380
VC 1000/N2RI	218	1x112	1x112	8	12	357	-	-	33	460	70	434	488	-	-	-	-	-	17	447
VC 1000/N2	218	1x112	1x112	8	12	357	-	-	33	460	70	434	488	-	-	-	-	-	17	467
VC 1000/N2	218	1x112	1x112	8	12	381	-	-	39	500	80	506	568	-	-	-	-	-	19	522
VC 1120/N2RI	236	1x112	1x112	8	12	421	-	-	39	540	80	556	616	-	-	-	-	-	19	700
VC 1120/N2	236	1x112	1x112	8	12	421	-	-	39	540	80	556	616	-	-	-	-	-	19	730
VC 1120/N2	236	1x112	1x112	8	12	501	-	-	39	600	60	604	690	-	-	-	-	-	19	795